

(12) United States Patent Suzuki

US 6,359,649 B1 (10) Patent No.:

(45) Date of Patent: *Mar. 19, 2002

VIDEO CAMERA INTEGRATED WITH STILL CAMERA

- (75) Inventor: Etsurou Suzuki, Kanagawa-ken (JP)
- Assignee: Canon Kabushiki Kaisa, Tokyo (JP)
- (*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year

154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

patent term provisions of 35 U.S.C.

(21) Appl. No.: 08/625,548

(22)Filed: Apr. 1, 1996

(30)Foreign Application Priority Data

(51)	Int. Cl. ⁷		H04N 5/225
(52)	U.S. Cl.		
(= a)	T14 1 7 0	~	• • • • • • • • • • • • • • • • • • • •

Field of Search 348/220, 333, 348/372, 371, 370, 334, 373, 375, 64, 315; 358/906, 909.1; 396/374, 429; H04N 5/232

(56)**References Cited**

U.S. PATENT DOCUMENTS

4,829,384 A	*	5/1989	Iida et al 358/229
4,841,359 A	*	6/1989	Hawkins et al 358/76
5,387,928 A	*	2/1995	Nishimura 348/70
5,416,560 A	*	5/1995	Taka 354/471
5,453,796 A	*	9/1995	Duffield et al 348/565
5,497,193 A	*	3/1996	Mitsuhashi et al 348/231
5,546,121 A	*	8/1996	Gotanda et al 348/64
5,734,424 A	*	3/1998	Sasaki 348/220

5,883,666	Α	*	3/1999	Kyuma et al	348/220
5,899,581	Α	*	5/1999	Kawamura et al	348/220
5,923,816	Α	*	7/1999	Ueda	348/220
5,956,082	Α	*	9/1999	Yamazaki	348/222
6,037,972	Α	*	3/2000	Horiuchi et al	348/64
6,069,994	Α	*	5/2000	Kozuki et al	348/220
6,130,710	Α	*	10/2000	Yasuda	348/220

FOREIGN PATENT DOCUMENTS

JP	5-110947	*	4/1993	 H04N/5/278

* cited by examiner

Primary Examiner—Wendy R. Garber Assistant Examiner—Jacqueline Wilson (74) Attorney, Agent, or Firm-Robin, Blecker & Daley

ABSTRACT

In a video camera integrated with a still camera in which the still camera and the video camera are integrated into one camera body, while photography is not being performed by the video camera, an image immediately preceding an image to be recorded by the still camera and an image immediately following the image recorded by the still camera can be displayed on a monitor of the video camera. While photography is being performed by the video camera, the display of images before and after the execution of photography by the still camera is inhibited. When the camera is equipped with a flash device and still camera recording is accompanied by a flash emission, control is effected such that image information is stored for one field which is recorded by the video camera and which does not include image information for one field which does not contain an emission of the flash device is displayed. Alternatively, during flashing, an exposure value of the video camera may be made approximately equal to a correct exposure value that allows the still camera to achieve a correct exposure during flashing and display is made of a stored field which contains the emission of the flash device.

24 Claims, 17 Drawing Sheets

